



AIRMASTER™ DELUXE FAIRING WITH AUDIO SYSTEM 1340

FITS: UNIVERSAL FITMENT

PARTS INCLUDED

- 1 AirMaster Deluxe Fairing with Audio System
1 Fairing Wiring Kit
1 Dragon Wing Spacer Kit
1 iPod Docking cord
1 3.5mm Audio Cable
2 Cigarette Lighter/Power Points
1 GPS rubber block mount
1 Stereo "Weather" cover
1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING! THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Set of Sockets and a Ratchet, Combination and Hex Wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

PROCEDURE

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface; turn off the ignition and allow the engine to cool.

STEP 2 You will need to determine the appropriate mounting kit for your application. (Sold Separately)

CONNECTING POWER WIRES

STEP 3 Gain access to the battery - refer to your owners manual for location of the battery

CUSTOMER SERVICE
877.370.3604 (toll free)

INSTALLATION QUESTIONS
techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
• The product must be properly installed, maintained and operated under normal conditions.
• Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
• Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
• Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
• Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
• Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today-select the "CATALOGS" icon. Each Kuryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.

-cont.-



STEP 4 Remove the instrument panel.(Dash Panel) or route the wiring harness under the tank. Plug the harness from the fairing to the wiring harness, route the wiring harness back to the battery.

STEP 5 Take the wiring harness ends and connect positive and negative fork terminals to the positive and negative mounts on the battery. (Note: the positive wire has an in-line fuse.)

STEP 6 Connect the wire labeled "switch power" to keyed 12V power. This allows the stereo to power up only when the key is in the "On" position.

NOTE Connecting this wire to constant power will result in battery drain.

STEP 7 Tuck the wiring harness away and re-mount the instrument panel or tank. Secure any excess wiring out of the way and replace the seat.

FAIRING OPTIONS

- Within the fairing, you will have many different options that will make the fairing very user friendly.
- Inside the glove box you will find a non-slide rubber mat, a GPS rubber block mount, an iPod docking cord, a 3.5 audio cable, a cigarette lighter/power point, keys, stereo instructions and the stereo "weather" cover. Also, a spacer kit is included that will be needed if you wish to install the Küryakyn Dragon Wings sold separately. (Küryakyn P/N 1117 or 1108)

NOTE The Dragon Wing spacer kit is needed when installing the Küryakyn Dragon wings; they allow smooth operation of the Dragon Wings. Place the spacers behind the center and top Dragon Wing mounting hole locations.

- The iPod docking cord is the black cord with the protected cap that you will have to remove to plug the iPod in. This cord is a power (charging) cord as well as the cord that communicates the iPod to the radio in the fairing.
- You also have a 3.5mm audio cable that has to be used if you are using any other MP3 player that does not have an iPod docking location. Simply plug the 3.5mm cable into the front of the radio (small end) and connect the opposite end to the MP3 player's headphone jack.
- The cigarette lighter/power point is for use for any type of charging you may need (i.e. cell phone ect. . .) You may also use it for the lighter function. The fairing also has an alternative cigarette lighter/power point. It is located to the lower left hand side just below the handlebars.
- The GPS rubber block mount is an option that we provided to make the installation of a GPS easier. On the inside of the fairing storage compartment door, you will find four pre-formed holes that line up with the rubber block mount. Using a drill, you can drill the four holes on the inside of the fairing storage compartment door. Once the holes are drilled, you will be able to take the rubber block mount and place it between the GPS and the fairing storage compartment door to help absorb some of the vibration from the bike as well as allowing the GPS to mount flat on the door.
- The Stereo "weather" cover is needed when you wish to wash the bike or for use when you store the bike. Remove the radio trim bezel and place the tabs on the right side of the weather cover into the two slots on the right side of the stereo opening. Gently snap the left side into place and make sure that it is securely in place.

ATTENTION! When washing your bike, try to avoid excessive water around the stereo and speaker areas. Too much water contact could potentially damage the components in this fairing.

Ride On!